

New Products Announced in 2017

RADOME OMNIs (BATONS)	
RO5805NF	Radome Omni, 4900-6000 MHz, N Female connector, 5dBi
RO8605NFC	Radome Omni 860-930 MHz, N Female connector, 5 dBi
ROKIT	Bracket for RO8605NFC
RO25002NM	Radome Omni, 2300-2700 MHz, N Male connector, 2 dbi
W5067	Radome Omni, Multi-band 698-960/1710-2170/2400-2700 MHz, N Female, .7/1/2 dBi
W5030	Radome Omni, Multi-band 2.4-2.5/5.15-5.875 GHz, N Male Connector
RO5810NF	Radome Omni, 4900-6000 MHz, N Female connector, 5dBi
RO5810NM	Radome Omni, 4900-6000 MHz, N Female connector, 5dBi
5Bar (PS + Carrier DAS) and	
PSDAS4310F	Ant DAS In-Building Omni-Directional 380-520/698-6000Mhz 4.3/10-female;
PSDAS4310FP	Ant DAS In-Building Omni-Directional 380-520/698-6000Mhz 4.3/10-female; -155dBc PIM
PSDASNF	Ant DAS In-Building Omni-Directional 380-520/698-6000Mhz N-female
PSDASNFP	Ant DAS In-Building Omni-Directional 380-520/698-6000Mhz N-female; -155dBc PIM
DASUTLC500NF	Ant Clarity® Clear Ultra Low Clearance Omni, 608-2700 MHz
Panther Multi-Band Vehicular Updates	
GPSMB401	ANT MiMoLTE, DB-WiFi, GNSS Vehicle Mount White
GPSMB502	ANT MiMoLTE, MiMo DB-WiFi, GNSS Vehicle Mount White
Stealth Blade Updates	
SB698SMA3	Stealth Blade 698-906/1710-2170/2300-2700 MHz, 3' RG-316, SMA
SB698SMA12	Stealth Blade 698-906/1710-2170/2300-2700 MHz, 3' RG-316, SMA

ICEFIN	
ICEFIN24DMN	Low Profile Clarity IP67 2400-2500 MHz, Direct Mount
ICEFIN24NMOHF	Low Profile Clarity IP67 2400-2500 MHz, NMO Mount required
ICEFIN49DMN	Low Profile Clarity IP67 4900-6000 MHz, Direct Mount
ICEFIN49NMOHF	Low Profile Clarity IP67 4900-6000 MHz, NMO Mount required
ICEFIN698/869DMN	Low Profile Clarity IP67, 2.6 dBi, 698-869 MHz, Direct Mount
ICEFIN698/960NMO	Low Profile Clarity IP67 3.04 dBi, 698-960 MHz, NMO Mount required
ICEFIN806DMN	Low Profile Clarity IP67, 3.7 dBi, 806-960 MHz, Direct Mount
ICEFIN806NMO	Low Profile Clarity IP67, 2.91 dBi, 806-960 MHz, NMO Mount required
ICEFINLDMN	Low Profile Clarity IP67. 3.1/5.17 dBi, 698-960/1710-2700 MHz, Direct Mount
ICEFINLNMOHF	Low Profile Clarity IP67, 698-960/1710-2700 MHz, NMO Mount required
ICEFINWDMN	Low Profile Clarity IP67, 2400-2500/4900-6000 MHz, Direct mount
ICEFINWNMOHF	Low Profile Clarity IP67, 2400-2500/4900-6000 MHz, NMO Mount required
ICEFIN-F	Ceiling Flange Ring, Antenna, 2.54" OD,
ICEFIN-GP	Ground Plane, 15.8" OD, Aluminum
LTE DIPOLES	
W5084	External antenna LTE 698-2690 MHz Swivel Dipole TNC connector IP65
W5084K	External antenna LTE 698-2690 MHz Swivel Dipole SMA connector IP65
W5095	External antenna LTE Multi-Band TNC connector IP65
W5095K	External antenna LTE Multi-Band SMA male connector IP65
700/800 and Wideband 450 and MagMt w/ LMR240	
KGI768	ANT, GLS MT, 700 800MHz,
LP78NMO	ANT, LOW PROFILE 740-960MHz, VEH MT
LPT450/512NMO	LPT 450-520MHZ ANTENNA
KG3E768UD	On Glass 764-869MHZ ANTENNA 14' UD coax
NMOMMR240NOCONN	NMO 3.5" Round Mag Mount, 12' LMR240 NO CONN